

- PRODUCT DATA SHEET -

Product Name:	OT Fouling-Release (long version: OT Fouling-Release Tape)
Tape Type:	Multi-layer, biocide-free, self-fusing silicone tape coated with fouling-release silicone
Surface:	Fouling-Release-Silicon, black, protected with blue PE-Film
Colour:	black
Thickness:	
Silicon Tape:	0,700 mm
Fouling-Release:	0,170 mm
Protective Film:	0,050 mm

1.1	Core	paper or plastic, 67mm, inner diameter
1.2	Width	100-300 mm
1.3	Core width	Depending on production width
1.4	Roll length	10 m – 100 m
1.5	Winding	Protective film outside, fouling release inside
1.6	Transport	In separate boxes or in collective box
1.7	Packing	Boxes depending on product size(s)
1.8	Labelling	Labels on the box
1.9	Storage	At least 1 year (dry, below 23°C, no direct sunlight)
2.0	Adhesion	At least 1 N/5cm (following DIN 53 357/A)
2.1	Elongation at brake	Over 300% (following 53504 S1)
2.2	Antifouling	Static fouling free for at least 30 days; dynamic fouling free for at least 5 years (following ASTM 6990-03 and ASTM 3623-78A)

OT Fouling-Release Tape contains no biocides, toxins or other hazardous or prohibited ingredients.

However, it is not always possible to exclude minor impurities of the raw material or the film. This can lead to the tape having such substances in the trace range. The analysis of such substances is not necessarily part of our quality assurance system. We provide this product information based on our current knowledge and experience and cannot guarantee or accept responsibility for factors beyond our control or knowledge.